

**SAFETY DATA SHEET**

H3502

Page 1

Issued: 22/07/2005

Revision No: 1

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING****Product name:** H3502 Toluene free**Use / description of product:** Edge fix sealer**Company name:** Heskins Ltd

Churchill Road Industrial Estate

Brinscall

Chorley

PR6 8RQ

United Kingdom

Tel: +44 (0) 1254-832266

Fax: +44 (0) 1254-832476

**2. COMPOSITION / INFORMATION ON INGREDIENTS****Hazardous ingredients:** ETHYL ACETATE 10-30%

EINECS: 205-500-4 CAS: 141-78-6

[F] R11; [Xi] R36; [Xi] R66; [-] R67

⌋ ACETONE 10-30%

EINECS: 200-662-2 CAS: 67-64-1

[F] R11; [Xi] R36; [Xi] R66; [-] R67

⌋ ETHYL METHYL KETONE 30-50%

EINECS: 201-159-0 CAS: 78-93-3

[F] R11; [Xi] R36; [Xi] R66; [-] R67

**3. HAZARDS IDENTIFICATION****Main hazards:** Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.**Other hazards:** In use, may form flammable / explosive vapour-air mixture.**4. FIRST AID MEASURES (SYMPTOMS)****Skin contact:** There may be irritation and redness at the site of contact.**Eye contact:** There may be irritation and redness. The eyes may water profusely.**Ingestion:** There may be soreness and redness of the mouth and throat.**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.**4. FIRST AID MEASURES (ACTION)****Skin contact:** Remove from skin with paper or towel. Wash effected area thoroughly with soap and water. Seek medical advice if symptoms persist.

[cont...]

**SAFETY DATA SHEET**

H3502 TOLUENE FREE

Page 2

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

**Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Workplace exposure limits**

**WEL (8 hr exposure limit):** 200ppm

**WEL (15 min exposure limit):** 400ppm

**Hazardous ingredients:** ETHYL ACETATE

WEL (8 hr exposure limit): 200 ppm WEL (15 min exposure limit): 400 ppm

## ⌋ ACETONE

WEL (8 hr exposure limit): 1210 mg/m<sup>3</sup> WEL (15 min exposure limit): 3620 mg/m<sup>3</sup>

## ⌋ ETHYL METHYL KETONE

WEL (8 hr exposure limit): 600 mg/m<sup>3</sup> WEL (15 min exposure limit): 899 mg/m<sup>3</sup>

[cont...]

**SAFETY DATA SHEET**

H3502 TOLUENE FREE

Page 3

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, or when spraying, compressed airline breathing apparatus should be used.

**Hand protection:** Avoid skin contact. For repeated exposure use Viton or 4H chemical gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Colour:** Colourless

**Odour:** Characteristic odour

**Evaporation rate:** Fast

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Insoluble

**Viscosity:** Viscous

**Boiling point/range°C:** 56

**Flammability limits %: lower:** 1.8

**upper:** 13

**Flash point°C:** -19

**Autoflammability°C:** 460

**Relative density:** 0.86

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions. Stable at room temperature.

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Hazardous ingredients:** ETHYL ACETATE

ORL MUS LD50 4100 mg/kg

ORL RAT LD50 5620 mg/kg

SCU RAT LDLO 5 gm/kg

II ACETONE

IVN RAT LD50 5500 mg/kg

ORL MUS LD50 3 gm/kg

ORL RAT LD50 5800 mg/kg

**SAFETY DATA SHEET**

H3502 TOLUENE FREE

Page 4

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Volatile.

**Persistence and degradability:** Biodegradable in part only.

**Bioaccumulative potential:** No data available.

**13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** Arrange for disposal by a licenced waste disposal company

**Disposal of packaging:** Arrange for disposal by a licenced waste disposal company

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

**UN no:** 1133

**ADR Class:** 3

**Packing group:** II

**Classification code:** F1

**Shipping name:** ADHESIVES

**Labelling:** 3

**Hazard ID no:** 33

**IMDG / IMO**

**UN no:** 1133

**Class:** 3

**Packing group:** II

**EmS:** F-E,S-D

**Marine pollutant:** .

**Labelling:** 3

**IATA / ICAO**

**UN no:** 1133

**Class:** 3

**Packing group:** II

**Packing instructions:** 305(P&CA); 307(CAO)

**Labelling:** 3

**15. REGULATORY INFORMATION**

**Hazard symbols:** Highly flammable.

Irritant.



**Risk phrases:** R36: Irritating to eyes.

[cont...]

**SAFETY DATA SHEET**

H3502 TOLUENE FREE

Page 5

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S2: Keep out of the reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S3/9/49: Keep only in the original container in a cool, well-ventilated place.

S33: Take precautionary measures against static discharges.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour.

S29/35: Do not empty into drains; dispose of this material and its container in a safe way.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Risk phrases used in s.2:** R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.