

Heskins Ltd H3404 Thick Safety-Grip® data sheet

ANTI-SLIP SOLUTIONS

Subject	Result	Test method
Back carrier	2mm PVC	Caliper method
Type of adhesive	Solvent acrylic	N/A
Total thickness	2.12mm	Caliper method
Mineral type	Aluminium Oxide	N/A
Adhesion to steel (g/25.4mm ²)	1500↑	PSTC-4
Temperature range	-30°C to +70°C	See notes below
Maximum size of production roll	1168mm x 50m	N/A
Resistance to water (months)	10	PSTC-35
Resistance to chemicals (months)	8	PSTC-35
Resistance to motor oil	Excellent	PSTC-35
Life (months)	12 to 24	PSTC-9

The independent test laboratory at Adhesive Technical Services Ltd performed the temperature test, England (test results available)

Coefficient of friction data

	Dry surface test result	Wet surface test result
H3404	102 TRL	71 TRL

The above tests were conducted in accordance with Pendulum, the tests were conducted at a recognised independent friction testing laboratory, and copy certificates are available on request. Pendulum is a dynamic test, for static tests, we also have results ASTM C 1028-96.

LRV Test Results

Material/Colour	Av. LRV	Range
H3404Y (Yellow)	39.67	2.12
H3404N (Black)	0	0

The test procedure follows Lucideon In House Test Method WW22, and complies with the requirements of BS.8493:2008+A1:2010.

All the above data is for reference only.

©Heskins Ltd 1997-2022