



ANTI-SLIP SOLUTIONS  
[mail@heskins.com](mailto:mail@heskins.com)

[www.heskins.com](http://www.heskins.com)

29/03/2022

## Heskins H3427 Removable Safety-Grip® data sheet

Subject	Result	Test method
Back carrier	0.1mm PVC + 0.01mm PET	Caliper method
Type of adhesive	Solvent acrylic	N/A
Mineral type	Aluminium Oxide	N/A
Adhesion to steel (kg/25.4mm <sup>2</sup> )	0.3↑	PSTC-4
Temperature range	-5°C to +50°C	See notes below
Maximum size of production roll	1168mmx100m	N/A
Resistance to water	Good	PSTC-35
Life (months)	12 to 24	PSTC-9

*The independent test laboratory at Adhesive Technical Services Ltd performed the temperature test, England (test results available)*

### LRV Test Results

Material/Colour	Av. LRV	Range
H3427Y (Yellow)	46.8	4
H3427N (Black)	0.5	1
H3427D (Black)	0.75	2
H3427D (Yellow)	81.5	3

The test procedure follows Lucideon In House Test Method WW22, and complies with the requirements of BS.8493:2008+A1:2010.

All the above data is for reference only.

©Heskins LTD 1997-2022

