

## Heskins Ltd H6632 ECEI04 Approved Reflective Tape data sheet

Subject	Result
<b>Durability sealing</b>	Full longitudinal permanent heat sealing
<b>Colours</b>	Red, white or yellow are the approved colours
<b>Film</b>	PC
<b>Type of adhesive</b>	Modified solvent acrylic
<b>Reflective base thickness</b>	0.22mm
<b>Adhesive thickness</b>	0.06mm
<b>Thickness of carrier film</b>	0.07mm
<b>Upper film thickness</b>	0.1mm
<b>Applied thickness</b>	0.45mm
<b>Temperature range</b>	-30°C to +80°C

*The independent test laboratory at Adhesive Technical Services Ltd performed the temperature test, England (test results available)*

### Reflection values

Colours	White	Yellow	Red
<b>Average coefficient of retroreflection values/cd(lx:m<sup>2</sup>)</b>	360	270	65

### LRV Test Results

Material/Colour	Av. LRV	Range
H6632R (Red)	19.96	7.67
H6632Y (Yellow)	39.41	15.41
H6632W (White)	57.72	16.39

The test procedure follows Lucideon In House Test Method WW22, and complies with the requirements of BS.8493:2008+A1:2010.

All the above data is for reference only.  
©Heskins Ltd 1997-2022