

H3427 Removable Safety-Grip™ Data Sheet

Subject	Result	Test Method
Back carrier	0.1mm PVC + 0.01mm PET	Caliper method
Type of adhesive	Solvent acrylic	N/A
Mineral type	Aluminium Oxide	N/A
Adhesion to steel (kg/25.4mm ²)	0.3↑	PSTC-4
Temperature range	-5°C to +50°C	See notes below
Maximum size of production roll	1168mm x 100m	N/A
Resistance to water	Good	PSTC-35
Life (months)	12 to 24	PSTC-9

LRV Test Results

SKU (Colour)	RAL	Pantone	Av. LRV	Range
H3427N (Black)	9004	Black U	0.3	0.1
H3427Y (Yellow)	1003	115 U	48.4	1.4
H3427D (Black/ Yellow Hazard)	9004 / 1003	Black / 112 U	0.7 / 81.5	2 / 3

The independent test laboratory at Adhesive Technical Services Ltd performed the temperature test, England (test results available)

The above tests were conducted in accordance with Pendulum, the tests were conducted at a recognised independent friction testing laboratory, and copy certificates are available on request. Pendulum is a dynamic test, for static tests, we also have results ASTM C 1028-96.

All the above data is for reference only.

©Heskins Ltd 1997-2024